



## Item #69582

Radiant White Laser Label / TP170 @ 1.30 Cwt. / 2.5 Mil Laser Liner L-5

### FACESTOCK

#### Radiant White Laser Label

A 50# bright white, smooth facestock that provides excellent toner printing anchorage for sheet-fed ink jet and laser printers. Also performs well with continuous form laser printers and pricemark label gun printing.

**Type:** Paper

**Caliper:** 3.50 Mil

**Opacity:** 90.0

**Brightness:** 94

**Basis Weight:** 50lbs/3300 sq ft

**Tensile:** MD: 29 Lbs/in, CD: 17 Lbs/in

**Tear:** MD: 47 Grams, CD: 51 Grams

**Elongation:** MD: N/A, CD: N/A

#### REGULATORY APPROVAL

**RoHS:** Yes

**REACH:** Yes

**CPSIA:** Yes

**Prop 65:** Yes

**TPCH:** Yes

**Indirect Food:** Yes

**Direct Food:** No

**UL:**

### ADHESIVE

#### TP170 @ 1.30 Cwt.

A general purpose acrylic adhesive showing good initial tack with high shear and high ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

**Adhesive Type:** Permanent Acrylic

**Shear:** 300 min.

**Minimum Application Temperature:** 35 F

**Service Temperature:** 65- F to 180 F

#### TYPICAL ADHESION VALUES

**Stainless Steel:** 180° Peel: 5.2 lb/in,

Loop Tack: 2.20 lb/in<sup>2</sup>

**Glass:** 180° Peel: 3.2 lb/in

**Polyethylene:** 180° Peel: 1.6 lb/in

**Corrugated:** 180° Peel: 3.4 lb/in

**Painted Metal:** 180° Peel: 4.6 lb/in

#### REGULATORY APPROVAL

**RoHS:** Yes

**REACH:** Yes

**CPSIA:** Yes

**Prop 65:** Yes

**TPCH:** Yes

**Indirect Food:** Yes

**Direct Food:** No

**UL:**

### RELEASE LINER

#### 2.5 Mil Laser Liner L-5

A bleached kraft liner which has been silicone coated one side to give a controlled release. It is designed to withstand die-cutting and has excellent layflat characteristics while providing outstanding dimensional stability.

**Basis Weight:** 0 lb/ream

**Tensile:** MD: 24 lb/in, CD: 10

**Caliper:** 2.5 mil

**Tear:** MD: N/A, CD: N/A

#### REGULATORY APPROVAL

**RoHS:** Yes

**REACH:** Yes

**CPSIA:** Yes

**Prop 65:** Yes

**TPCH:** Yes

**Indirect Food:**

**Direct Food:**

**UL:**

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. TECHNICOTE will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages. TECHNICOTE warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), TECHNICOTE shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with TECHNICOTE'S standards, correct such defects by suitable repair or replacement without charge at TECHNICOTE's plant or at the location of the products (at TECHNICOTE's election); provided, however, if TECHNICOTE determines that repair or replacement is not commercially practical, TECHNICOTE shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

TECHNICOTE CORPORATE HEADQUARTERS 222 Mound Avenue Miamisburg, OH 45342 800-358-4448 [technicote.com](http://technicote.com)