



# Not a Current Stock Product - Please contact Technical Services at 800-358-4448 for assistance.

3.4 mil Dual Digital White Flexible Vinyl / Ultra-Removable Adhesive / 80# Score Back

## FACESTOCK

### 3.4 mil Dual Digital White Flexible Vinyl

A smooth flexible top coated vinyl film suitable for HP Indigo Presses, EFI Jetrion 4900, and Durst Tao UV ink jet presses. It has chemical and moisture resistance as well as high durability for outdoor label applications

**Type:** Film  
**Caliper:** 3.4  
**Opacity:** N/A  
**Brightness:** 87  
**Basis Weight:** N/A  
**Tensile:** MD: 3800, CD: 3300  
**Tear:** MD: N/A, CD: N/A  
**Elongation:** MD: 120, CD: 240

#### REGULATORY APPROVAL

**RoHS:** Yes  
**REACH:**  
**CPSIA:** Yes  
**Prop 65:** Yes  
**TPCH:** Yes  
**Indirect Food:** Yes  
**Direct Food:** No  
**UL:** No

## ADHESIVE

### Ultra-Removable Adhesive

An ultra-removable emulsion acrylic adhesive with low tack on smooth flat surfaces that can be cleanly removed after extended periods of time. This adhesive is suitable for glass, counter tops, painted metal, smooth painted walls, and stainless steel. This adhesive should be qualified for end-use suitability.

**Adhesive Type:** Removable Acrylic  
**Shear:**  
**Minimum Application Temperature:** -15°F  
**Service Temperature:** -60 to 160°F

**TYPICAL ADHESION VALUES**  
**Stainless Steel:** 180° Peel: 0.0 lb/in,  
Loop Tack: 0.00 lb/in<sup>2</sup>  
**Glass:** 180° Peel: 0.0 lb/in  
**Polyethylene:** 180° Peel: 0.0 lb/in  
**Corrugated:** 180° Peel: 0.0 lb/in  
**Painted Metal:** 180° Peel: 0.0 lb/in

#### REGULATORY APPROVAL

**RoHS:** Yes  
**REACH:** Yes  
**CPSIA:** Yes  
**Prop 65:** Yes  
**TPCH:** Yes  
**Indirect Food:** Yes  
**Direct Food:** No  
**UL:** No

## RELEASE LINER

### 80# Score Back

This liner is clay-coated bleached kraft designed for roll-to-sheet applications. It is manufactured with scores every 1.25" apart.

**Basis Weight:** 84 lb/ream  
**Tensile:** MD: 36 lb/in, CD: 21  
**Caliper:** 4.6 mil  
**Tear:** MD: N/A, CD: N/A

#### REGULATORY APPROVAL

**RoHS:** Yes  
**REACH:** Yes  
**CPSIA:** Yes  
**Prop 65:** Yes  
**TPCH:** Yes  
**Indirect Food:** Yes  
**Direct Food:** No  
**UL:** No

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. TECHNICOTE will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages. TECHNICOTE warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), TECHNICOTE shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with TECHNICOTE'S standards, correct such defects by suitable repair or replacement without charge at TECHNICOTE's plant or at the location of the products (at TECHNICOTE's election); provided, however, if TECHNICOTE determines that repair or replacement is not commercially practical, TECHNICOTE shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.