

Item #5616

1 Mil Polyester NTC Clear / OL-1 / 8 Pt Tag (100#) L-3

FACESTOCK

1 Mil Polyester NTC Clear

An optically clear film used primarily for overlaminating purposes. It has exceptionally high strength and superior durability for protecting labels in harsh environments. This film is not meant to be printed on, but will accept some inks due to a natural dyne level.

Type: Film Caliper: 1.00 Mil Opacity: N/A Brightness: N/A Basis Weight: N/A

Tensile: MD: 28000 Psi, CD: 34000 Psi **Tear:** MD: 1400 Grams, CD: N/A **Elongation:** MD: 300, CD: 110

REGULATORY APPROVAL

RoH5: Yes REACH: Yes CPSIA: Yes Prop 65: Yes TPCH: Yes Indirect Food: Yes Direct Food: No

UL: No

ADHESIVE

OL-1

An acrylic emulsion adhesive recommended only for overlaminating films. It offers maximum clarity and minimum cold flow while providing good resistance to moisture, plasticizers, UV and solvents.

Adhesive Type: Permanent Acrylic

Shear: 280 min.

Minimum Application Temperature: 35 F **Service Temperature:** 65- F to 200 F

TYPICAL ADHESION VALUES **Stainless Steel:** 180° Peel: 4.8 lb/in,

Loop Tack: 2.00 lb/in²
Glass: 180° Peel: 2.8 lb/in
Polyethylene: 180° Peel: 1.2 lb/in
Corrugated: 180° Peel: 3.0 lb/in
Painted Metal: 180° Peel: 4.2 lb/in

REGULATORY APPROVAL

RoHS: Yes REACH: Yes CPSIA: Yes Prop 65: Yes TPCH: Yes Indirect Food: Yes

Direct Food: Yes

UL:

RELEASE LINER 8 Pt Tag (100#) L-3

An 8pt, 100# tag liner which has been silicone coated one side to give a controlled release. It has exceptionally high internal strength to withstand all conventional processing operations including die-cutting, perforating, fanfolding and refolding processes.

Basis Weight: O lb/ream Tensile: MD: 70 lb/in, CD: 32 Caliper: 8.0 mil Tear: MD: N/A. CD: N/A

REGULATORY APPROVAL

RoHS: Yes REACH: Yes CPSIA: Yes Prop 65: Yes TPCH: Yes Indirect Food: UL:

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. TECHNICOTE will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages. TECHNICOTE warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), TECHNICOTE shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with TECHNICOTE's standards, correct such defects by suitable repair or replacement without charge at TECHNICOTE's plant or at the location of the products (at TECHNICOTE's election); provided, however, if TECHNICOTE determines that repair or replacement is not commercially practical, TECHNICOTE shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.