



Not a Current Stock Product - Please contact Technical Services at 800-358-4448 for assistance.

4 Mil Vinyl TC Flexible White / Re-Po / 80# -0-Score

FACESTOCK

4 Mil Vinyl TC Flexible White

A 4 mil flexible white vinyl with polymeric plasticizers, formulated to provide optimum performance with pressure sensitive adhesives. The top-coating provides outstanding adhesion to various printing inks.

Type: Film
Caliper: 4.0
Opacity: 90.0
Brightness: N/A
Basis Weight: N/A
Tensile: MD: 3900 lb/in, CD: 3800 lb/in
Tear: MD: 100 Grams, CD: 100 Grams
Elongation: MD: N/A, CD: N/A

REGULATORY APPROVAL

RoHS: Yes
REACH: Yes
CPSIA: Yes
Prop 65: Yes
TPCH: Yes
Indirect Food: Yes
Direct Food: No
UL:

ADHESIVE

Re-Po

A specialty microsphere removable acrylic adhesive designed for clean removability and repositionability from plastics and painted metal. Not recommended for curved or textured surfaces.

Adhesive Type: Removable Acrylic
Shear: NA
Minimum Application Temperature: 40°F
Service Temperature: 20 to 140°F

TYPICAL ADHESION VALUES
Stainless Steel: 180° Peel: 0.8 lb/in,
Loop Tack: 0.00 lb/in²
Glass: 180° Peel: 1.2 lb/in
Polyethylene: 180° Peel: 0.8 lb/in
Corrugated: 180° Peel: 0.8 lb/in
Painted Metal: 180° Peel: 0.8 lb/in

REGULATORY APPROVAL

RoHS: Yes
REACH: Yes
CPSIA: Yes
Prop 65: Yes
TPCH: Yes
Indirect Food: Yes
Direct Food: No
UL: No

RELEASE LINER

80# -0-Score

A bleached kraft which has been silicone coated one side to give a controlled release. This paper has high internal strength to withstand all conventional processing operations including die-cutting and butt-cutting.

Basis Weight: 80 lb/ream
Tensile: MD: 51 lb/in, CD: 0
Caliper: 4.6 mil
Tear: MD: N/A, CD: N/A

REGULATORY APPROVAL

RoHS: Yes
REACH: Yes
CPSIA: Yes
Prop 65: Yes
TPCH: Yes
Indirect Food: Yes
Direct Food: No
UL: No

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. TECHNICOTE will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages. TECHNICOTE warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), TECHNICOTE shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with TECHNICOTE'S standards, correct such defects by suitable repair or replacement without charge at TECHNICOTE's plant or at the location of the products (at TECHNICOTE's election); provided, however, if TECHNICOTE determines that repair or replacement is not commercially practical, TECHNICOTE shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

TECHNICOTE CORPORATE HEADQUARTERS 222 Mound Avenue Miamisburg, OH 45342 800-358-4448 technicote.com