Technicote®

Not a Current Stock Product - Please contact Technical Services at 800-358-4448 for assistance.

3.4 mil Dual Digital White Flexible Vinyl / Ultra-Removable Adhesive / 80# Score Back

FACESTOCK

3.4 mil Dual Digital White Flexible Vinyl

A smooth flexible top coated vinyl film suitable for HP Indigo Presses, EFI Jetrion 4900, and Durst Tao UV ink jet presses. It has chemical and moisture resistance as well as high durability for outdoor label applications

Type: Film
Caliper: 3.4
Opacity: N/A
Brightness: 87
Basis Weight: N/A
Tensile: MD: 3800, CD: 3300
Tear: MD: N/A, CD: N/A
Elongation: MD: 120, CD: 240

REGULATORY APPROVAL
RoHS: Yes
REACH:
CPSIA: Yes
Prop 65: Yes
TPCH: Yes
Indirect Food: Yes
Direct Food: No
UL: No

ADHESIVE

Ultra-Removable Adhesive

An ultra-removable emulsion acrylic adhesive with low tack on smooth flat surfaces that can be cleanly removed after extended periods of time. This adhesive is suitable for glass, counter tops, painted metal, smooth painted walls, and stainless steel. This adhesive should be qualified for end-use suitibility.

Adhesive Type: Removable Acrylic
Shear:
Minimum Application Temperature: -15°F
Service Temperature: -60 to 160°F

TYPICAL ADHESION VALUES
Stainless Steel: 180° Peel: 0.0 lb/in, Loop Tack: 0.00 lb/in^2
Glass: 180° Peel: 0.0 lb/in
Polyethylene: 180° Peel: 0.0 lb/in
Corrugated: 180° Peel: 0.0 lb/in
Painted Metal: 180° Peel: 0.0 lb/in

REGULATORY APPROVAL
RoHS: Yes
REACH: Yes
CPSIA: Yes
Prop 65: Yes
TPCH: Yes
Indirect Food: Yes
Direct Food: No
UL: No

RELEASE LINER

80# Score Back

This liner is clay-coated bleached kraft designed for roll-to-sheet applications. It is manufactured with scores every 1.25" apart.

Basis Weight: 84 lb/ream
Tensile: MD: 36 lb/in, CD: 21
Caliper: 4.6 mil
Tear: MD: N/A, CD: N/A

REGULATORY APPROVAL
RoHS: Yes
REACH: Yes
CPSIA: Yes
Prop 65: Yes
TPCH: Yes
Indirect Food: Yes
Direct Food: No
UL: No

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. TECHNICOTE will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages. TECHNICOTE warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), TECHNICOTE shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with TECHNICOTE'S standards, correct such defects by suitable repair or replacement without charge at TECHNICOTE's plant or at the location of the products (at TECHNICOTE's election); provided, however, if TECHNICOTE determines that repair or replacement is not commercially practical, TECHNICOTE shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

TECHNICOTE CORPORATE HEADQUARTERS 222 Mound Avenue Miamisburg, OH 45342 800-358-4448 technicote.com