



Not a Current Stock Product - Please contact Technical Services at 800-358-4448 for assistance.

TP800

ADHESIVE

TP800

TP800 is a high performance all-temp hot melt adhesive with quick initial tack and outstanding adhesion to common packaging films at subzero temperatures.

Adhesive Type: Permanent Hot Melt

Shear: 80 Hrs

Minimum Application Temperature: -20°F

Service Temperature: -20°F to 160°F

TYPICAL ADHESION VALUES

Stainless Steel: 180° Peel: 4.1 lb/in,
Loop Tack: 5.40 lb/in²

Glass: 180° Peel: 3.4 lb/in

Polyethylene: 180° Peel: 4.8 lb/in

Corrugated: 180° Peel: 1.2 lb/in

Painted Metal: 180° Peel: 2.8 lb/in

REGULATORY APPROVAL

RoHS: Yes

REACH: Yes

CPSIA: Yes

Prop 65: Yes

TPCH: Yes

Indirect Food: Yes

Direct Food: No

UL:

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. TECHNICAL will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages. TECHNICAL warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), TECHNICAL shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with TECHNICAL'S standards, correct such defects by suitable repair or replacement without charge at TECHNICAL'S plant or at the location of the products (at TECHNICAL'S election); provided, however, if TECHNICAL determines that repair or replacement is not commercially practical, TECHNICAL shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

TECHNICOTE CORPORATE HEADQUARTERS 222 Mound Avenue Miamisburg, OH 45342 800-358-4448 technicote.com