

1.5 Mil Acetate Matte Clear / TS523 @ 1.50 Cwt. / 1.5 mil Clear Polyester

Facestock(1.5 Mil Acetate Matte Clear): A 1.5 mil matte clear film with excellent ink receptivity and printability.

Type:	Film	Basis Weight:	N/A	<u>Regulatory Approval</u>	
Caliper:	1.50 Mil	Tensile:	MD: 20 Lbs/in CD: 25 Lbs/in	RoHS:	Yes
Opacity:	N/A	Tear:	MD: N/A CD: N/A	REACH:	Yes
Brightness :	N/A	Elongation :	MD: 325 CD: N/A	CPSIA:	Yes
				Prop 65:	Yes
				TPCH:	Yes
				Indirect Food:	Yes
				Direct Food:	No
				UL:	No

Adhesive(TS523 @ 1.50 Cwt.): A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent and occasional water and oil resistance. This is an acid free adhesive.

Adhesive Type:	Permanent Acrylic	<u>Typical Adhesion Values</u>		<u>Regulatory Approval</u>	
Shear:	350 min.	Stainless Steel:	180° Peel: 5.6 lb/in Loop Tack: 2.70 lb/in ²	RoHS:	Yes
Minimum Application Temperature :	35 F	Glass:	180° Peel: 2.8 lb/in	REACH:	Yes
Service Temperature :	-65 F to 200 F	Polyethylene:	180° Peel: 2.9 lb/in	CPSIA:	Yes
		Corrugated:	180° Peel: 4.0 lb/in	Prop 65:	Yes
		Painted Metal:	180° Peel: 4.6 lb/in	TPCH:	Yes
				Indirect Food:	Yes
				Direct Food:	No
				UL:	

Release Liner(1.5 mil Clear Polyester): "A 1.5 mil polyester liner which has been silicone coated one side to give a controlled release. It has extremely high internal strength for ease in manufacturing, converting and end usage, making it an outstanding liner for high speed, automatic applications."

Basis Weight:	0 lb/ream	Caliper:	1.5 mil	<u>Regulatory Approval</u>	
Tensile:	MD: 33000 lb/in	Tear:	MD: N/A	RoHS:	Yes
				REACH:	Yes
				CPSIA:	Yes
				Prop 65:	Yes
				TPCH:	Yes
				Indirect Food:	
				Direct Food:	
				UL:	

in connection with such use. TECHNICOTE will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages. TECHNICOTE warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), TECHNICOTE shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with TECHNICOTE'S standards, correct such defects by suitable repair or replacement without charge at TECHNICOTE's plant or at the location of the products (at TECHNICOTE's election); provided, however, if TECHNICOTE determines that repair or replacement is not commercially practical, TECHNICOTE shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.