

1.5 Mil Acetate Matte Clear / TS523 @ 1.50 Cwt. / 65# FBK L-3

Facestock(1.5 Mil Acetate Matte Clear): A 1.5 mil matte clear film with excellent ink receptivity and printability.

Type:	Film 1.50 Mil	Basis Weight: Tensile:	N/A			Regulatory Approval
					RoHS:	Yes
Caliper:			MD: 20 Lbs/in	CD: 25 Lbs/in	REACH:	Yes
Opacity:	N/A	Tear:	MD: N/A	CD: N/A	CPSIA:	Yes
Brightness	N/A	Elongation	MD: 325	CD: N/A	Prop 65:	Yes
:		:			TPCH:	Yes
					Indirect Food:	Yes
					Direct Food:	No
					UL:	No

Adhesive(TS523 @ 1.50 Cwt.): A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent and occasional water and oil resistance. This is an acid free adhesive.

Adhesive	Permanent	Typical Adhesion Values	Regulatory Approval	
Type:	Acrylic	Stainless Steel:	RoHS:	Yes
Shear:	350 min.	180° Peel: 5.6 lb/in	копэ.	163
	_	Loop Tack: 2.70 lb/in ²	REACH:	Yes
Minimum Application Temperature : Service Temperature :	35 F	Glass:	CPSIA:	Yes
		180° Peel: 2.8 lb/in		.,
		Polyethylene:	Prop 65:	Yes
	-65 F to 200 F	180° Peel: 2.9 lb/in	TPCH:	Yes
	-65 F to 200 F	Corrugated:	Indirect Food:	Yes
		180° Peel: 4.0 lb/in		
		Painted Metal:	Direct Food:	No
		180° Peel: 4.6 lb/in	UL:	

Release Liner(65# FBK L-3): "A fully bleached kraft liner which has been silicone coated one side to give a controlled release. This paper has high internal strength to withstand all conventional processing operations including die-cutting, perforating, fanfolding and refolding processes."

Basis Weight:	0 lb/ream	Caliper:	3.8 mil	Regulatory Approval	
Tensile:	MD: 33 lb/in	Tear:	MD: N/A	RoHS:	Yes
				REACH:	Yes
				CPSIA:	Yes
				Prop 65:	Yes
				TPCH:	Yes
				Indirect Food:	
				Direct Food:	
				UL:	

in connection with such use. TECHNICOTE will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages. TECHNICOTE warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), TECHNICOTE's shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with TECHNICOTE'S standards, correct such defects by suitable repair or replacement without charge at TECHNICOTE's plant or at the location of the products (at TECHNICOTE's election); provided, however, if TECHNICOTE determines that repair or replacement is not commercially practical, TECHNICOTE shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

TECHNICOTE,INC.

222 MOUND AVENUE

MIAMISBURG, OH 45342

800-358-4448

FAX: 937-859-9096

www.technicote.com