

Classic Crest 60# Wet Strength Solar White / TS585WS @ 1.60 Cwt. / 44# PK L-4

Facestock(Classic Crest 60# Wet Strength Solar White): 60# Fine Textured uncoated paper face sheet with internal wet strength properties. Most commonly used for wine label that is exposed to cold wet conditions.

Type:	Paper	Basis Weight:	60 # Rm 25 x 38	<u>Regulatory Approval</u>	
Caliper:	4.30 Mil	Tensile:	MD: 9 Lbs/in CD: 6 Lbs/in	RoHS:	Yes
Opacity:	90.0	Tear:	MD: 67 Grams CD: 59 Grams	REACH:	Yes
Brightness :	91	Elongation :	MD: N/A CD: N/A	CPSIA:	Yes
				Prop 65:	Yes
				TPCH:	Yes
				Indirect Food:	Yes
				Direct Food:	No
				UL:	

Adhesive(TS585WS @ 1.60 Cwt.): A specialty adhesive designed to adhere to slightly wet surfaces with good ultimate adhesion when applied at temperatures as low as -20 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for hard to label substrates.

Adhesive Type:	Permanent Acrylic	<u>Typical Adhesion Values</u>		<u>Regulatory Approval</u>	
Shear:	65 min.	Stainless Steel:	180° Peel: 4.8 lb/in Loop Tack: 2.70 lb/in²	RoHS:	Yes
Minimum Application Temperature :	20- F	Glass:	180° Peel: 3.2 lb/in	REACH:	Yes
Service Temperature :	65- F to 140 F	Polyethylene:	180° Peel: 2.0 lb/in	CPSIA:	Yes
		Corrugated:	180° Peel: 3.3 lb/in	Prop 65:	Yes
		Painted Metal:	180° Peel: 4.1 lb/in	TPCH:	Yes
				Indirect Food:	Yes
				Direct Food:	No
				UL:	

Release Liner(44# PK L-4): "A medium weight natural kraft coated 1 side (C1S) with a gloss polyethylene. Silicone coating has been added on the gloss side (C1S) for a controlled release. It has superb smoothness, excellent dimensional stability and exceptional layflat characteristics."

Basis Weight:	44 lb/ream	Caliper:	3.2 mil	<u>Regulatory Approval</u>	
Tensile:	MD: 0 lb/in	Tear:	MD: N/A	RoHS:	Yes
				REACH:	Yes
				CPSIA:	Yes
				Prop 65:	Yes
				TPCH:	Yes
				Indirect Food:	
				Direct Food:	
				UL:	

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. TECHNICOTE will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages. TECHNICOTE warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), TECHNICOTE shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with TECHNICOTE'S standards, correct such defects by suitable repair or replacement without charge at TECHNICOTE's plant or at the location of the products (at TECHNICOTE's election); provided, however, if TECHNICOTE determines that repair or replacement is not commercially practical, TECHNICOTE shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

TECHNICOTE,INC.	222 MOUND AVENUE	MIAMISBURG, OH 45342	800-358-4448	FAX:: 937-859-9096	www.technicote.com
-----------------	------------------	----------------------	--------------	--------------------	--